




▶ **HEAVY CUT**
FAST CUT
FINISH
SUPER FINISH



- ▶ **Level of cut:** 10/10
- ▶ **Level of gloss:** 5/10
- ▶ **Colour:** white
- ▶ **Odour:** light and pleasant
- ▶ **Physical form:** creamy
- ▶ **Storage:** 5-30°C

CODES

Code	Size	Pcs/Box
(EU) 600711	325 g	24
(EU) 600707	1,3 kg	12
(US) 600693	8 oz	24
(US) 600689	32 oz	12

PRODUCT DESCRIPTION

Water based and silicon free high cutting compound used to remove P1200-P2000 sand scratches, as well as deep marks, failings and dullness, according to the hardness of treated paints. It restores badly oxidized surfaces as well as can be used on new well dried paints.

The key feature of PAICAR 01 is offering a strong cutting power when surfaces are in critical conditions. According to wished final quality and finish, and especially on dark coloured surfaces, it is recommended to follow up with a finer compound, such as PAICAR 03.

PAICAR 01 has been developed to give its best in combination with a rotor-bital polishing machine and DA-01 red hard foam pad. It may be used also in combination with SL3 lamb wool pad and a rotary machine, for higher cutting action.

HOW TO USE

Apply a small quantity of PAICAR 01 on DA-01 red foam pad and use the pad for spreading the compound on the surface. Select a rotor-bital polisher and start at low RPM, then gradually increase revolutions and polish with crossed movements, namely left to right, up and down. Wipe the surface with a clean Silky Tech microfiber cloth, in order to remove any potential residue. For higher cutting action, select a rotary polisher and follow the same procedure, starting slow (800 RPM), and increasing gradually to 1500 RPM. In combination with rotary machine, SL3 lamb wool pad can be used for powering the cut level.

TIPS

- ▶ Clean surface thoroughly before polishing
- ▶ Shake well before use
- ▶ Apply a small amount of compound
- ▶ Polish with crossed movements: left to right, up and down
- ▶ Use rotary polisher for powering the cut level
- ▶ Use DA-01 Red hard polishing pad for standard condition
- ▶ Keep the polishing pad clean to speed up polishing process and maximise pad life
- ▶ Use SL3 lamb wool for badly oxidized surfaces
- ▶ Use a clean Silky Tech microfiber to wipe off without too much pressure